


[IEEE HOME](#) | [SEARCH IEEE](#) | [SHOP](#) | [WEB ACCOUNT](#) | [CONTACT IEEE](#)[Membership](#) [Publications/Services](#) [Standards](#) [Conferences](#) [Careers/Jobs](#)Welcome
United States Patent and Trademark[Help](#) [FAQ](#) [Terms](#) [IEEE Peer Review](#) [Quick Links](#)

Welcome to IEEE Xplore

- [Home](#)
- [What Can I Access?](#)
- [Log-out](#)

Tables of Contents

- [Journals & Magazines](#)
- [Conference Proceedings](#)
- [Standards](#)

Search

- [By Author](#)
- [Basic](#)
- [Advanced](#)

Member Services

- [Join IEEE](#)
- [Establish IEEE Web Account](#)
- [Access the IEEE Member Digital Library](#)

 [Print Format](#)

[Home](#) | [Log-out](#) | [Journals](#) | [Conference Proceedings](#) | [Standards](#) | [Search by Author](#) | [Basic Search](#) | [Advanced Search](#)
[Join IEEE](#) | [Web Account](#) | [New this week](#) | [OPAC Linking Information](#) | [Your Feedback](#) | [Technical Support](#) | [Email Alerting](#)
[No Robots Please](#) | [Release Notes](#) | [IEEE Online Publications](#) | [Help](#) | [FAQ](#) | [Terms](#) | [Back to Top](#)

Copyright © 2002 IEEE — All rights reserved

EAST [firsttime.wsp:1]

File View Edit Tools Window Help

Pending Active Failed Saved

L1: (32730) phase adj locked adj loop
L2: (1) 1 and synchronous adj triggered
L3: (677) 1 and (phase adj frequency adj detector)
L4: (65) 3 and d adj flip adj flop

DBs: USPAT, US-PCPUB, EPO, JPO, DERWENT, IBM_TDB

Default operator: OR Plurals Highlight all hit terms initially

3 and d adj flip adj flop

BRG t... ISR Image Text HTML

| U | I | Document ID | Issue Date | Pages | Title | Current DR | Current XRef |
|---|-------------------------------------|-------------------|------------|-------|---|------------|--------------|
| 1 | <input type="checkbox"/> | US 20030038691 A1 | 20030227 | 41 | System and method of digital tuning a voltage controlled oscillator | 331/1A | |
| 2 | <input checked="" type="checkbox"/> | US 20030038661 A1 | 20030227 | 8 | Apparatus to decrease the spurs level in a phase-locked loop | 327/157 | |
| 3 | <input checked="" type="checkbox"/> | US 20030001681 A1 | 20030102 | 19 | Method and device for improving efficiency of frequency synthesizer | 331/18 | |
| 4 | <input checked="" type="checkbox"/> | US 20020135400 A1 | 20020926 | 11 | Digital frequency comparator | 327/40 | |
| 5 | <input checked="" type="checkbox"/> | US 20020118006 A1 | 20020829 | 40 | Phase frequency detector | 324/76.53 | |
| 6 | <input checked="" type="checkbox"/> | US 20020114416 A1 | 20020822 | 41 | Phase alignment of data to clock | 375/373 | |
| 7 | <input checked="" type="checkbox"/> | US 20020109553 A1 | 20020815 | 41 | Voltage controlled oscillator | 331/36C | |
| 8 | <input checked="" type="checkbox"/> | US 20020109552 A1 | 20020815 | 40 | System and method of tuning a voltage controlled oscillator | 331/36C | |
| 9 | <input checked="" type="checkbox"/> | US 20020109527 A1 | 20020815 | 40 | High-speed output driver | 326/83 | |

Hits Details HTML

Ready NUM